

20231.
Lisa G. Gray
Lisa G. Gray



DRAWINGS
FOR
APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: **SYNCHRONIZATION OF RECURRING RECORDS IN INCOMPATIBLE DATABASES**

APPLICANT: **DAVID J. BOOTHBY**

"EXPRESS MAIL" Mailing Label Number EM121269025US

Date of Deposit November 13, 1996
I hereby certify under 37 CFR 1.10 that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office To Addressee" with sufficient postage on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

USA G Gray
USA G Gray

08/752490



PATENT
ATTORNEY DOCKET NO: 05110/006001

SYNCHRONIZATION OF RECURRING
RECORDS IN INCOMPATIBLE DATABASES

5

Reference to Microfiche Appendix

An appendix (appearing now in paper format to be replaced later in microfiche format) forms part of this application. The appendix, which includes a source code listing relating to an embodiment of the invention, includes

10

691 frames on 8 microfiche
frames on microfiche.

This patent document (including the microfiche appendix) contains material that is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document as it appears in the Patent and Trademark Office file or records, but otherwise reserves all copyright rights whatsoever.

15

Background of the Invention

20

This invention relates to synchronizing incompatible databases.

25

Databases are collections of data entries which are organized, stored, and manipulated in a manner specified by applications known as database managers (hereinafter also referred to as "Applications"). The manner in which database entries are organized in a database is known as the data structure. There are generally two types of database managers. First are general purpose database managers in which the user determines (usually at the outset, but subject to future revisions) what the data structure is.

30

These Applications often have their own programming language and provide great flexibility to the user. Second are special purpose database managers that are specifically designed to create and manage a database having a preset

data structure. Examples of these special purpose database managers are various scheduling, diary, and contact manager Applications for desktop and handheld computers. Database managers organize the information in a database into
5 records, with each record made up of fields. Fields and records of a database may have many different characteristics depending on the database manager's purpose and utility.

Databases can be said to be incompatible with one
10 another when the data structure of one is not the same as the data structure of another, even though some of the content of the records is substantially the same. For example, one database may store names and addresses in the following fields: FIRST_NAME, LAST_NAME, and ADDRESS.
15 Another database may, however, store the same information with the following structure: NAME, STREET_NO., STREET_NAME, CITY_STATE, and ZIP. Although the content of the records is intended to contain the same kind of information, the organization of that information is
20 completely different.

It is often the case that users of incompatible databases want to be able to synchronize the databases. For example, in the context of scheduling and contact manager Applications, a person might use one Application on the
25 desktop computer at work ^{and} ~~while~~ another on his handheld computer or his laptop computer at home. It is desirable for many of these users to be able to synchronize the entries on one with entries on another. However, the incompatibility of the two databases creates many problems
30 that need to be solved for successful synchronization. The U.S. patent and copending patent application of the assignee hereof, IntelliLink Corp., of Nashua, New Hampshire (U.S. Patent No. 5,392,390; U.S. Application, Serial No.

B
08/371,194, filed on January 11, 1995, ^{now U.S. Patent No. 5,684,990,} incorporated by reference herein) show two methods for synchronizing incompatible databases and solving some of the problems arising from incompatibility of databases. However, other
5 problems remain.

One kind of incompatibility is when one database manager uses recurring records. Recurring records are single records which contain information which indicates that the records actually represent multiple records sharing
10 some common information. Many scheduling Applications, for example, permit as a single record an event which occurs regularly over a period of time. Instances of such entries are biweekly committee meetings or weekly staff lunches. Other scheduling Applications do not use these types of
15 records. A user has to create equivalent entries by creating a separate record for each instance of these recurring events.

Various problems arise when synchronizing these types of records. Let us consider a situation when
20 Application A uses recurring records while Application B does not. A synchronizing application must be able to create multiple entries for B for each recurring entry in A. It also must be able to identify some of the records in database B as instances of recurring records in database A.
25 Also, many Applications which allow recurring records also permit revision and editing of single instances of recurring records without affecting the master recurring record. Moreover, single instances of a recurring event in Application B may be changed or deleted. The recurring
30 master may also be changed which has the effect of changing all instances. These changes make it harder to identify multiple entries in database B as instances of a recurring record in database A. Moreover, synchronization must take

these changes into account when updating records in one or the other database.

Summary of the Invention

5 The invention provides a technique for synchronizing
databases in which different techniques are used for storing
a recurring event. A database in which the recurring event
is, for example, stored as a single recurring record can be
synchronized with a database in which the same recurring
event is stored as a series of individual records. The
10 individual records are processed to form a synthetic
recurring record representing the set of individual records,
and synchronization decisions are based on a comparison of
the synthetic record to the recurring record of the other
database. Following synchronization, the synthetic record
15 can be "fanned" back into the individual records to update
the database containing individual records, and the updated
recurring record can be written back to the other database.
In this way, the invention avoids the problems encountered
with prior methods, in which synchronization resulted in a
20 recurring record being transformed into a series of
individual records.

30 The invention features a computer implemented method
of synchronizing at least a first and a second database,
wherein the manner of storing a set of recurring instances
differs between the first and second databases, and at least
25 the first database uses a recurring record to store the set
of recurring instances. A plurality of instances in the
second database are processed to generate a synthetic
recurring record representing recurring instances in the
second database, the synthetic recurring record of the
30 second database is compared to a recurring record of the

first database, and synchronization is completed based on the outcome of the comparison.

Preferred embodiments of the invention may include one or more of the following features: Completing
5 synchronization may include adding, modifying, or deleting the synthetic recurring record or the recurring record. Following synchronization, the synthetic recurring record may be fanned back into a plurality of single instances. The set of recurring instances may be stored in the second
10 database as a plurality of single instances. The set of recurring instances may be stored in the second database as a recurring record having a different record structure than the recurring record of the first database. A history file may be stored containing a record representative of the
15 presence of a recurring record or a synthetic recurring record in past synchronizations.

The invention may be implemented in hardware or software, or a combination of both. Preferably, the technique is implemented in computer programs executing on
20 programmable computers that each include a processor, a storage medium readable by the processor (including volatile and non-volatile memory and/or storage elements), at least one input device, and at least one output device. Program code is applied to data entered using the input device to
25 perform the functions described above and to generate output information. The output information is applied to one or more output devices.

Each program is preferably implemented in a high level procedural or object oriented programming language to
30 communicate with a computer system. However, the programs can be implemented in assembly or machine language, if desired. In any case, the language may be a compiled or interpreted language.

Each such computer program is preferably stored on a storage medium or device (e.g., ROM or magnetic diskette) that is readable by a general or special purpose programmable computer for configuring and operating the computer when the storage medium or device is read by the computer to perform the procedures described in this document. The system may also be considered to be implemented as a computer-readable storage medium, configured with a computer program, where the storage medium so configured causes a computer to operate in a specific and predefined manner.

Other features and advantages of the invention will become apparent from the following description of preferred embodiments, including the drawings, and from the claims.

Brief Description of the Drawing

Figure 1 is a schematic drawing of the various modules constituting the preferred embodiment.

Figure 2 is a representation of the Workspace data array.

Figure 3 is the pseudocode for the Translation Engine Control Module.

Figure 4 is the pseudocode for generating the parameter Table.

Figure 5 is the pseudocode for fanning a recurring record.

Figure 6 is the pseudocode for the Synchronizer loading the History File.

Figure 7 is the pseudocode for matching key fields (Key_Field_Match).

Figure 8 is the pseudocode for loading records of B_Database into Workspace.

5 *Ins* Figure 26 ^{cle} is the look up table for determining unloading outcome results.

Ins Figure 27 ^{cle} is the pseudocode for fanning recurring records of A-Database for unloading.

Figure 28 is the pseudocode for unloading the History File.

B Figure 29 is a table showing ^{cases in which Recurring Masters are fanned} ~~cases for fanning~~ [^] ~~Recurring Masters~~ into own database.

B Figure 30 is the pseudocode for loading records by a fast synchronization Translator. ^{loading}

Ins Figure 31 ^{cle} is the pseudocoe ^{loading} for ~~loadin~~ records by a fast synchronization Translator.

Description of the Preferred Embodiments

15 Fig. 1 shows the relationship between the various modules of the preferred embodiment. Translation Engine 1 comprises Control Module 2 and Parameters Table Generator 3. Control Module 2 is responsible for controlling the synchronizing process by instructing various modules to perform specific tasks on the records of the two databases
20 being synchronized. The steps taken by this module are demonstrated in Fig. 3. The Parameters Table Generator 3 is responsible for creating a Parameter_Table 4 which is used by all other modules for synchronizing the databases. Details of the Parameter_Table are described in more detail
25 below. The Synchronizer 15 has primary responsibility for carrying out the core synchronizing functions. It is a table-driven code which is capable of synchronizing various types of databases whose characteristics are provided in the Parameter_Table 4. The Synchronizer creates and uses the
30 Workspace 16, which is a temporary data array used during the synchronization process.

5 A Translator 5 (A_Translator) is assigned to the
A_database 13 and another Translator 9 (B_Translator) to the
B_database 14. Each of the database Translators 5 and 9
comprises three modules: Reader modules 6 and 10 (A_Reader
and B_Reader), which read the data from the databases 13 and
14; Unloader modules 8 and 12 (A_Unloader and B_Unloader),
which analyze and unload records from the Workspace into the
databases 13 and 14; and Sanitizing modules 7 and 11
(A_Sanitizer and B_Sanitizer), which analyze the records of
10 the other database loaded into the Workspace and modify them
according to rules of data value of its own database. In
the preferred embodiment, the modules of the A_Translator 5
are designed specifically for interacting with the
A_database 13 and the A_Application 17. Their design is
15 specifically based on the record and field structures and
the rules of data value imposed on them by the
A_Application, the Application Program Interface (API)
requirements and limitations of the A_Application and other
characteristics of A_Database and A_Application. The same
20 is true of the modules of B_Translator 9. These Translators
are not able to interact with any other databases or
Applications. They are only aware of the characteristics of
the database and the Application for which they have been
designed. Therefore, in the preferred embodiment, when the
25 user chooses two Applications for synchronization, the
Translation Engine chooses the two Translators which are
able to interact with those Applications. In an alternate
embodiment, the translator can be designed as a table-driven
code, where a general Translator is able to interact with a
30 variety of Applications and databases based on the
parameters supplied by the Translation Engine 1.

Referring to Figs. 1, 2 and 3, the synchronization
process is as follows. The Parameter_Table 4 is generated

by the Parameter Table Generator 3. The Synchronizer 15 then creates the Workspace 16 data array and loads the History File 19 into the Workspace 16. The B_Reader module 11 of the B_Translator reads the B_database records and sends them to the Synchronizer for writing into the Workspace. Following the loading of B_Database records, the A_Sanitizer module 8 of the A_Translator 5 sanitizes the B_Records in the Workspace. The A_Reader module 7 of the A_Translator 5 then reads the A_Database records and sends them to the Synchronizer 16 for writing into the Workspace. The B_Sanitizer module 12 of the B_Translator 9 then sanitizes the A_Records in the Workspace. The Synchronizer then performs the Conflict Analysis and Resolution (CAAR) on the records in Workspace. At the end of this analysis the user is asked whether he/she would like to proceed with updating the A_ and B_databases. If so, the B_Unloader module of the B_Translator unloads the appropriate records into the B_database. The A_Unloader module 6 then performs the same task for the A_Database. Finally, the Synchronizer creates a new History File 19.

Fig. 3 is the pseudocode for the preferred embodiment of the Control Module 2 of the Translation Engine 1. Control Module 2 first instructs the Parameter Table Generator 3 of the Translation Engine 1 to create the Parameter_Table (Step 100). ^{Figs. 4A and 4B are} Fig. 4 is the pseudocode for the preferred embodiment of the Parameter Table Generator module 3. The user is first asked to choose whether to use a previously chosen and stored set of preferences or to enter a new set of preferences (Step 150). Steps 151-165 show the steps in which the user inputs his/her new preferences. In step 152, the user chooses whether to perform a synchronization from scratch or an incremental synchronization. In a synchronization from scratch,

then calculates and stores in the Parameter_Table the Start_Current_Date_Range and End_Current_Date_Range values, the two variables indicating the starting point and the ending point of the date range for the current
5 synchronization session (step 173-174).

In steps 174 and 175, various parameters identifying the characteristics of the A_Database and Application and B_Database and Application are loaded from a database (not shown) holding such data for different Applications. These
10 are in turn stored in the Parameter_Table. One of the sets of parameters loaded and stored in the Parameter_Table is the Field_List for the two databases. The Field_List_A and Field_List_B contain the following information about each field in the data structure of the two databases:

- 15 1. Field name.
 2. Field Type.
 3. Field Limitations.
 4. No_Reconcile Flag.
 6. Key_Field Flag.
20 7. Mapped_Field Flag.

Field name is the name given to the field which the Translator for this Application uses. This name may also be the name used by the Application. Field Type identifies to the Synchronizer 15 the nature of the data in a field, e.g.,
25 Data, Time, Boolean, Text, Number, or Binary. The Field Name does not supply this information to the Synchronizer. Field Limitations identifies the various limitations the database manager imposes on the contents of a field. These limitations include: maximum length of text fields, whether
30 the text field must be in upper-case, range of permissible values (for example, in ToDo records priority field, the range of permissible values may be limited from 1 to 4), and whether a single line or multiple line field.

No_Reconcile flag indicates whether a field is a No_Reconcile field, meaning that it will not be used to match records nor will it be synchronized although it will be mapped and possibly used in synchronization. Almost all fields will not be designated as No_Reconcile. However, sometimes it is necessary to do so. Key_Field flag indicates that a field should be considered as a key field by the Synchronizer 15.

Key fields are used by the Synchronizer in various stages of synchronization as will be discussed in detail below. The decision of identifying certain fields as key is based on examining the various Applications to be synchronized, their data structure, and the purpose for which the database is used. Such examination reveals which fields would best function as key fields for synchronization. For example, for an address book database, the lastname, firstname, and company name field may be chosen as key fields. For Appointments, the date field and the description field may be chosen as key fields.

Mapped_Field flag indicates whether a field is mapped at all. The Synchronizer uses this flag to determine whether it should use the A→B_Map or B→A_Map to map this field. Unlike a No_Reconcile field, an unmapped field will not be carried along through the synchronization.

Another set of parameters in the Parameter_Table identify the Translator Modules 13, 14 for the two Applications which the user has selected. Because each Application is assigned its own Translator, it is necessary to identify to the Command Module and the Synchronizer which Translators should be used.

In step 102 of Fig. 1, the Translation Engine instructs the Synchronizer to load the History File. History File is the file which was saved at the end of last

synchronization. It contains the history of the previous synchronization which is necessary for use with the current synchronization in case of Incremental Synchronization.

Records from the A_Database and B_Database are analyzed against the records of the history file to determine the changes, additions, and deletions in each of two databases since last synchronization and whether additions, deletions, or updates need to be done to the records of the databases.

Referring to ^{FMS. 5A and 5B,} ~~Fig. 5~~, in steps 200-201, the Synchronizer

finds the appropriate History file to be loaded. If Synchronization_from_Scratch flag is set, the History File is deleted (step 203). If no History File is found, the synchronization will proceed as if it was a synchronization from scratch (step 204). If the Field Lists stored in the History File are not the same as the current Field Lists in the Parameter_Table, or the mapping information is not the same, the synchronization will proceed as synchronization from scratch because the differences indicate that the History File records will not properly match the database records (steps 206-209).

In step 210, the Synchronizer uses the Field_List for database B to create the Workspace 16. It is a large record array which the Synchronizer uses during synchronization. Referring to Fig. 2, Workspace 16 consist of two sections. First, the Synchronizer uses the Field List for the B_Database to make a record array 21 which has all the characteristics of the B_Database record structure. In addition, in each record in the Workspace, certain internal fields are added. One field is _subtype containing Origin Tags. Two other fields, called Rep_Basic and Rep_Excl, are included for all Appointment and ToDo Sections. The Rep_Basic field gives a full description of

fanned instance. Fig. 6 sets out the preferred embodiment of the process of fanning a record.

Fanning of recurring records also takes into account another set of considerations regarding date range
5 limitations and usefulness of instances to the user.

First, fanning is limited to the applicable date range. Second, the number of fanned instances is limited. When synchronizing Databases A and B, the preferred embodiment permits different sets of limits on fanned
10 instances to be established for each Database. This, for example, assists with managing storage capacity of a memory-constrained handheld device when being synchronized with a database on a desktop PC.

If the current Date Range is large enough to
15 accommodate more than the maximum number of instances which might be generated, those instances will be chosen which are likely to be most useful to the user. In the preferred embodiment, it is assumed that future instances are always more useful than past instances, that near future instances
20 are more useful than distant future instances, and that recent past instances are more useful than distant past instances. Therefore, based on these assumptions, a fanning date range is calculated (Fig. 6, step 236).

Referring to Fig. 2, in the second step of creating
25 the Workspace, the Synchronizer establishes an Extended Index Array 20 which has an index entry associated with each entry in the record array. Each index contains the following variables:

1. Next_In_CIG:
- 30 2. Next_In_SKG:
3. Next_In_FIG
4. Key_Field_Hash
5. A_Unique_ID_Hash

SECRET

6. B_Unique_ID_Hash
7. Non_Key_Field_Hash
8. Non_Date_Hash
9. Exclusion_List_Hash
- 5 10. Start_Date&Time
11. End_Date&Time
12. Various bit flags

Next_In_CIG is a linkage word, pointing to next member of the same Corresponding Item Group (CIG). A CIG is a group of records, one from each database and the History File, if applicable, which represent the same entry in each of the databases and the History File. There may be one, two or three records in a CIG. Next_In_SKG is a linkage word, pointing to next member of the Same Key Fields Group (SKG). An SKG is a group of records having the same key fields. Next_In_FIG is a linkage word, pointing to the next member of the Fanned Instances Group (FIG). A FIG is the group of fanned instances which correspond to a single recurring record.

20 Key_Field_Hash is hash of all Key_Fields.
A_unique_ID_Hash is hash of unique ID, if any, assigned by A_Database. B_unique_ID_Hash is hash of unique ID, if any, assigned by B_Database. Non_Key_Field_Hash is hash of all Non-Key Match Field, a Match Field being any mapped field which is not flagged as No_Reconcile. Non_Date_Hash is hash of all Non-Date Non-Key Match Fields. Exclusion_List_Hash is hash of recurring record's exclusion list.

30 Start_Date&Time and End_Date&Time are used for Appointment and ToDo type record only, indicating the start and end date and time of the record. They are used to speed up comparing functions throughout the synchronization. Hash values are also used to speed up the process of comparison. The preferred embodiment uses integer hashes.

18

Hash value computation takes into account certain rules of data value for fields, as will be described in more detail below.

5 In the preferred embodiment, the record array 21 is stored on magnetic disk of a computer whereas the Extended Index 20 is held resident in memory. The Extended Indexes have record pointer fields which point to each of the records on the disk file.

10 The Control Module 2 now instructs the synchronizer to load the History File into the Workspace (Fig. 3, step 102). Referring to Fig. 6, the synchronizer loads the records beginning in first available spot in the Workspace (step 211). The Synchronizer then performs an analysis on
15 records (steps 212-228). The records are also checked against the current date range and those falling outside of it are marked appropriately for Fast synchronization function, which will be described below. In case of recurring records, if any of the instances is within the
20 current date range, then the recurring record itself will be considered within the current date range (steps 217-227).

25 The synchronizer then builds SKGs by finding for each history record one record which has matching key fields and by placing that record in the SKG of the history record (step 215-216). Referring to Fig. 7, steps 250-258 describe the Key_Field_Match function used for matching records for SKG.

30 When comparing two records or two fields, in the preferred embodiment, the COMPARE function is used. The COMPARE function is intelligent comparison logic, which takes into account some of the differences between the rules of data value imposed by the A_Application and the B_Application on their respective databases. Some examples

are as follows. The COMPARE function is insensitive to upper and lower case letters if case insensitive field attribute is present. Because some Applications require entries to be in all capital letter, the COMPARE function
5 ignores the differences between upper and lowercase letters. The COMPARE function takes into account any text length limitations. For example, when comparing "App" in the A_Database and "Apple" in the B_Database, the COMPARE function takes into account that this field is limited to
10 only 3 characters in the A_Database. It also takes into account limits on numerical value. For example, priority fields in the A_Application may be limited to only values up to 3, whereas in the B_Application there may not be any limitation. The COMPARE function would treat all values in
15 B_records above 3 as 3.

The COMPARE function may ignore various codes such as end of line characters. It may strip punctuation from some fields such as telephone numbers and trailing white space from text fields (i.e "Hello " is treated as
20 "Hello"). It also considers field mapping. For example, if the only line that is mapped by the A→B_Map is the first line of a field, then only that line is compared. When comparing appointment fields, because different databases handle alarm date and time differently when Alarmflag is
25 false, the COMPARE function treats them as equal even though the values in them are not the same. It skips Alarm Date and Time, if the Alarm Flag is False. It also ignores exclusion lists when comparing recurring records.

In an alternate embodiment, the COMPARE function may
30 take into account more complicated rules for data value of the two Applications, such as the rules for data value imposed by Microsoft Schedule+, described above. Such a COMPARE function may be implemented as a table driven code,

the table containing the rules imposed by the A_Application and the B_Application. Because the COMPARE function has a specific comparison logic and takes into account a number of rules, the hashing logic must also follow the same rules.

- 5 It should be noted that the COMPARE function is used throughout the preferred embodiment for field comparisons.

✓ Now that the History File is loaded into the Workspace, the Control Module 2 instructs the B_Translator 13 to load the B_Database records (Fig. 3, step 103).

- 10 Referring to Fig. 8, steps 300-308, the B_Reader module 11 of the B_Translator 13 loads each B_record which has the right Origin Tag, which will be explained in more detail below.

- 15 The record must also be within the loading date range, which is a concatenation of the previous and current date ranges. The B_Translator sends these records to the Synchronizer which in turn stores them in the Workspace. When synchronizing with a date range limitation, all records which fall within either the previous or the current date
20 ranges are loaded. The current date range is used during unloading to limit the unloading of the records to only those records which fall within the database's current date range. In an alternate embodiment of the invention, each database or Application can have its own date range for each
25 synchronization.

- Most Applications or databases permit record-specific and field-specific updates to a Database. But some Applications or databases do not. Instead the Translator for these Application must re-create the whole database from
30 scratch when unloading at the end of synchronization. These databases are identified as Rebuild_All databases. To accommodate this requirement all records from such a database must be loaded into the Workspace, so that they can

later be used to rebuild the whole database. These databases records, which would otherwise have been filtered out by the date range or the wrong origin tag filters, are instead marked with special flag bits as Out_Of_Range or Wrong_Section_Subtype. These records will be ignored during the synchronization process but will be written back unmodified into the database from which they came by the responsible Unloader module 6, 10.

Control Module 2 next instructs the A_Translator 5 to sanitize the B-records. Referring to Fig. 9, steps 350-361, the A_Sanitizer module 8 of the A_Translator 5 is designed to take a record having the form of an A_Record and make it conform to the specific rules of data value imposed by the A_Application on records of the A_Database.

A_Sanitizer is not aware which database's field and records it is making to conform to its own Application's format. It is only aware of the A_Application's field and record structure or data structure. Therefore, when it requests a field from the sanitizer using the A_Database field name, it is asking for fields having the A_Database data structure. The Synchronizer, in steps 375-387, therefore maps each record according to the B→A_Map. In turn, when the Synchronizer receives the fields from the A_SANITIZER, it waits until it assembles a whole record (by keeping the values in a cache) and then maps the record back into the B format using the A→B_Map.

How a record or a field is sanitized in step 354 and 357 depends on the rules of data value imposed by the A_Application. For example, all of the logic of intelligent comparison in the COMPARE function described above can be implemented by sanitization. However, sanitization is best suited for more complex or unique types of database rules for data value. For example, consider the Schedule+ rules

they already have the B_Database format. Therefore, the synchronizer 15 does not need to map them before sending them to the B_Sanitizer module 12 of the B_Translator 19. For the same reason, there is no need for them to be mapped once they are sent back by the B_Sanitizer after having been sanitized. Once all the records are loaded, the records will undergo the same orientation analysis that the B_Records underwent (Fig. 11).

At this point, all records are loaded into the Workspace. SKGs are complete since every record at the time of loading is connected to the appropriate SKG. CIGs now contain all records that could be matched based on unique IDs. At this point, the records in the Workspace will be analyzed according to Conflict Analysis and Resolution ("CAAR") which is set out in Fig. 12 and in more detail in Figs. 13-18 and corresponding detailed description.

First, in step 500, ID bearing fanned instances in the History File records are matched to the fanned instances in the ID bearing database from which they came. The records from the database which have remained unchanged are formed into a new FIG. A new Synthetic Master is created based on those records and joined to them. The records which have been changed or deleted since last synchronization are set free as single records. They also result in a new exclusion list being created based on an old exclusion list and these new single records.

Second, in step 501, matches are sought for the ID based CIGs which are the only CIGs so far created in order to increase the membership of those CIGs. Preferably an exact all fields match is sought between current members of a CIG and a new one. Failing that, a weaker match is sought.

Third, in step 502, master/instances match is sought between recurring records and non-unique ID bearing instances by trying to find the largest group of instances which match certain values in the Recurring Master.

5 Fourth, in step 503, the items remaining in the SKGs are matched up based on either exact all field match or master/instance match, or a weaker match.

Fifth, in step 501, the appropriate CIG_Types are set for all the CIGs. CIG_Types will determine what the
10 outcome of unloading the records will be.

Referring to Fig. 13, first step in CAAR is analyzing unique ID bearing Fanned Instance Groups. This analysis attempts to optimize using unique IDs assigned by databases in analyzing fanned instances of recurring
15 records.

The analysis is performed for all Recurring Masters (i.e. all recurring records) which have ID-bearing fanned instances (or FIG records) in the H_File (step 550). All FIG records in the History File associated with a Recurring
20 Master are analyzed (steps 551-559). They are all removed from the SKG. If a FIG record is a singleton CIG, it means that it was deleted from the database since the previous synchronization. Therefore, it is added to the New_Exclusion_List (step 553). If a FIG record is a
25 doubleton and is an exact match, it means that the record was not modified since the previous synchronization. In this case, the record from the database is also removed from SKG (step 555). If a FIG record is a doubleton but is not an exact match for its counterpart in the database, it means
30 that the record was changed in the database. The History File record is treated as a deletion and therefore added to the New_Exclusion_List. The modified record in the database, which does not match the recurring record any

longer, is treated as a free standing record un-associated with the Recurring Master (step 557).

5 Upon analysis of all FIG records, a new record, the Synthetic Master, is created and joined in a CIG with the Recurring Master (step 231-236). The Synthetic Master has the same characteristics as the Recurring Master, except that it has a new exclusion list which is a merger of the New_Exclusion_List and the Exclusion_List of the Recurring Master (step 563). Also a new FIG is created between the
10 Synthetic Master and the CIG-mates of all FIG records from the History File (step 565).

15 In steps 567-569, the Synchronizer checks to see if there are some instances of the Recurring Master which fall within the previous synchronization's date range but fall outside of the current synchronization's date range. If so, the Fan_Out_Creep flag is set, indicating that the date range has moved in such a way as to require the record to be fanned for the database before unloading the record. The Fan_Out_Creep flag is an increase in the value in the
20 Non_Key_Field Hash of the Recurring Master. In this way, the Recurring Master during the unloading of the records will appear as having been updated since the last synchronization and therefore will be fanned for the current date range.

25 In step 570, all the FIG records analyzed or created in this analysis are marked as Dependent_FIGs. This results in these records being ignored in future analysis except when the recurring records to which they are attached are being analyzed.

30 At the end of the above analysis, all the records having a unique ID assigned by their databases have been matched based on their unique ID. From this point onward, the records which do not have unique IDs must be matched to

other records based on their field values. In the preferred embodiment, there are two categories of field value matches: strong matches and weak matches. A strong match between two records that have matching key fields is when non-key fields of the two records match or it is a Recurring Master and a fanned instance match (Fig. 14, steps 606-610). Referring to Fig. 15, a weak match between two records that have matching key fields is when the following are true: each of the two records are from different origins, because two records from the same source should not be in a CIG (e.g., A_Database and History File); each is not a weak match for another record because there is no reason to prefer one weak match over another; each is not a Dependent_FIG since these records do not have an independant existence from their recurring masters; both records are either recurring or non-recurring since a recurring and a nonrecurring should not be matched except if one is an instance of the other in which case it is a strong match; and, in case of non-recurring, they have matching Key_Date_Field which is the same as the Start_Date in the preferred embodiment because items on the same date are more likely to be modified versions of one another.

Referring to Fig. 14, these two types of matching are used to match records to existing CIGs for History File records which have been created based on matching unique IDs. Only doubleton CIGs are looked at, because singleton CIGs are handled in step 504 of Fig. 12 and tripleton CIGs are complete (steps 601-604). If a strong match is found, then if the record was a weak match in another CIG, it is removed from that CIG, and new weak match is found for that CIG (612-614). While weak matches are left in SKGs in case they will find a strong match, strong matches are removed from their SKGs (step 614). If a strong match is not found,

then a weak match is sought (steps 617-620). All records in the CIG are removed from SKG if no weak match is found, because this means that there is no possibility of even a weak match for this record (step 619).

- 5 The next step in CAAR is finding non-unique ID bearing instances for recurring items (Fig. 12, step 503). Referring to ^{Figs. 16A and 16B,} ~~Fig. 16,~~ this analysis takes place only if the database from which instances matching a recurring record are sought does not provide unique ID or if we are
- 10 synchronizing from scratch (steps 650-653). The goal of this analysis is to find matching instances for each Recurring Master from a different source than the Recurring Master. This analysis counts the number of records in SKG of the Recurring Master which have matching Non_Date_Hash
- 15 value (steps 665-669). The group of matching SKG records having the same non_Date_Hash value and having the highest number of members (if the number of members exceeds 30% of unexcluded instances) is then formed into a
- 20 Homogeneous_Instances_Group (steps 670-672). A Synthetic Master is created using the Rep_Basic of the Recurring Master and using the values from the homogeneous instances group. An Exclusion list is created based on the items belonging to the recurrence pattern but missing from the Homogeneous_Instances_Group. The Synthetic Master is added
- 25 to the CIG of the Recurring Master (steps 673-678). A new FIG for the Synthetic Master is then created using the Homogeneous_Instances_Group (step 679). These records are removed from any CIGs to which they belonged as weak matches and new weak matches are sought for those CIGs (steps 680-
- 30 684). Since the records in Homogeneous_Instances_Group have now been matched to a recurring record, they are marked as Dependent_FIGs (step 683). The Recurring Master's CIG is

then marked with Fan_Out_Creep flag, if necessary (step 685).

5 The next step in CAAR is completing analysis of records in SKGs (Fig. 12, step 504). Referring to Fig. 17, this analysis attempts to increase the population of CIGs up to a maximum by finding key field based matches with records from a source different from those of the CIG records. This analysis is performed by analyzing all the records in the SKGs except for the singleton SKGs (steps 703 and 712). The first thing is to remove any members that have already been marked as WEAK matches attached to ID-based doubleton CIGs. Those are left in the SKG up to this point to allow for the possibility that a STRONG match would be found instead. But that is not possible any longer (steps 713-715). Once the weak matches have been removed, all remaining SKG members belong to singleton CIGs. Any non-singleton CIGs which are formed from here on will be purely key field based.

15 Throughout the remaining SKG Analysis we are careful not to seek H_Record-A_Record or H_Record-B_Record matches for unique ID-bearing Source, since that would violate the exclusively ID-based matching scheme that applies in such cases. Note however that an A_Record-B_Record match is acceptable even if both A_Database and B_Database are unique ID-bearing databases.

25 Given that Key Field should not be performed where ID based matches are available (or otherwise there may be matches between records with differing IDs), there are limits to how big CIGs can get at this point. If both A and B_Databases are unique ID-bearing, any remaining H_Record must remain in Singleton CIGs, because they are prohibited from forming key fields based matches with items from either databases. Such H_Records are simply removed from the SKG when they are encountered. If just one of the two databases

being synchronized is unique ID-bearing then the maximum population that any CIG can now attain is 2 (Fig. 18, steps 750-751). If neither database is unique ID bearing then the CIG_Max_Size is three. For every CIG which is analyzed in
5 Fig. 17, the CIG_Max_Size is set according to this logic. When a CIG reaches its maximum possible population all of its members are removed from the appropriate SKG.

First, strong matches for the H-records are searched for, before trying to find A-B matches. If both Databases
10 are non-unique ID-bearing then two strong matches for each H_Record, an H-A and an H-B match, are sought (steps 715-720). If finding a strong match results in reaching the CIG_Max_Size, all members of the CIG are removed from the SKG (step 721).

15 When maximum CIG population is 3, weak matches are sought for strong matching CIG doubleton in order to build triplet CIGs. The first weakly matching SKG member is added to the CIG (steps 722-728). Whether or not a weak match is found for any of the doubleton CIGs, its members are removed
20 from the SKG (step 726). As there are no strong matches left in the SKG, weak matches are found for any remaining SKG members and joined to them in CIGs (steps 722-725).

At this stage, all CIGs are built. They must now be examined to determine what needs to be done to these records
25 so that the databases are synchronized, i.e. whether the records in the CIGs need to be added, deleted or changed in the two databases. First step is determining the CIG_TYPE which represents the relation between the records. The following CIG types are defined, all using a 3-digit number
30 that represents values found for A_DATABASE, History File, and B_Database, respectively:

1. 001 - record is "new" in the B_DATABASE

2. 010 - record is present in History, but absent in both A_Database and B_Databases
 3. 100 - record is "new" in the A_Database
 4. 101 - record is "new" in both A_Database and B_DATABASE; same in both
 5. 102 - record is "new" in both A_Database and B_DATABASE; different in each (conflict)
 6. 110 - record deleted from B_DATABASE
 7. 011 - record deleted from A_Database
 - 10 8. 012 - record deleted from A_Database and changed on B_DATABASE (DEL vs CHANGE conflict)
 9. 210 - record changed on A_Database and deleted from B_DATABASE(DEL vs CHANGE conflict)
 10. 111 - record unchanged since previous synchronization
 - 15 11. 112 - record changed on B_DATABASE only since previous synchronization
 12. 211 - record changed on A_Database only since previous synchronization
 - 20 13. 212 - record changed identically on both since previous synchronization
 14. 213 - record changed differently on each since previous synchronization (conflict)
 15. 132 - a conflict (102 or 213) was resolved by forming a compromise value; Update both
 - 25 16. 13F - created when a 132 Update both CIG is Fanned into the B DATABASE
- Fig. 19A and 19B show*
Fig. 19 shows the method used for setting all
 except the last two CIG_Types which are set in other operations.

Four of the CIG types assigned above involve conflicts: 102, 213, 012, and 210. Conflicts are those instances where a specific conflict resolution rule chosen

The user may elect that A_Database records should always trump or win over B_database records. This option is implemented by changing the CIG type to 211 - the processing during unloading the records changes the record value in the B_Database to match the current record value in the A_Database.

The user may elect that B_Database records should always trump or win over B_database records. This option is implemented by changing the CIG type to 112 - the processing during unloading the records changes the record value in the A_Database to match the current record value in the B_Database.

The user may choose to be notified in case of any conflict. The user is notified via a dialog box 30, shown in Fig. 20, whenever a CIG type conflict of 102 or 213 arises. The dialog box shows the record that is involved in the conflict 31. It also shows the A_Database 32 and B_Database 33 values for all conflicting fields, in a tabular display, with Field Names appearing in the left column 34. A dropdown list (not shown) in the lower left hand corner of the dialog 37, offers a total of three choices - add, ignore, and update. The user may choose to add new records or ignore the conflict. The user may also choose that the A_Record or B_Record should be used to update the other record. The user may also decide to create a compromise record by choosing values of different fields and then choosing update option. In this case, the CIG type is changed to 132, which results in an updating both databases with the new record compromise record.

When the user has chosen to be notified in case of conflict, if the user chooses to ignore conflict or that either the record of the A_Database or the B_DATABASE should win, the CIG type is left as a conflict CIG type (102 or

33

213) and a separate Conflict Resolution Choice is stored in the FLAGS word associated with each CIG member.

The final step in setting CIG_Types is the process for dealing with difficulties which arise from exclusion lists. For example, in a triple Recurring Master CIG, suppose the History File Recurring Master does not have any excluded instances. The A_Record has the following exclusion list:

12/1/96, 12/8/96

10 The B_Record has the following exclusion list:

1/1/97, 1/8/97, 1/15/97, 1/22/97, 1/29/97

If comparison of the Recurring Masters includes comparing exclusion list Field Values, this set of changes would cause the Synchronizer to report a CIG type 213 conflict.

If the Conflict Resolution Option is set to A_Database record wins, then the outcome prescribed by the Synchronizer would be for the A_Database to keep its exclusion list as is and for the B_Database to make its exclusion list match that of the A_Database.

The result would be to have a lot of duplicate entries in both Databases. The A_Database would have five duplicate entries in January 97 - that is the five unmodified Recurring Master instances, plus the five modified instances added across from B_Database to A_Database. The B_Database would have five duplicate entries in January 97, since synchronization has wiped out the five exclusions that were previously recorded in the B_Database exclusion list.

Two steps are implemented for dealing with this problem. First, the COMPARE function does not take into account exclusion list differences when comparing recurring records. Second, referring to Fig. 21, any new exclusions

added on to one recurring record will be added to the other record. The merging of exclusion lists is done regardless of any updates or conflicts, even unresolved conflicts, between the A_Database and B_Database copies of a Recurring Master. One exception is for CIG type 102 conflict which is left unresolved where Exclusion lists are not merged, because the user has chosen to leave those records as they are.

10 In most cases where it is necessary to merge exclusion lists, the CIG types and/or the Conflict Resolution Choice to arrange for all necessary updates to be performed during the unloading phases of synchronization.

15 First, A_Database and B_Database records' exclusion lists are compared. In case of databases which do not permit recurring items, the exclusion list of the Synthetic Master is compared to the recurring record of the other database (step 852). If there is no difference, then nothing is done (step 853). If there are differences, then it is determined which exclusions appear only in one record. 20 This comparison always yields one of the following scenarios: (1) all one-side-only Exclusions are on the A_Database (so Exclusions should be added to the B_Database); (2) all one-side-only Exclusions are on the B_Database (so Exclusions should be added to the A_Database); and (3) there are one-side-only Exclusions on both sides (so Exclusions should be added to both databases).

30 In each of these cases a separate table is used to look up instructions, for how to handle each specific situation (Figs 22-24). The tables cover all possible combinations of previous CIG types and outcome codes with all possible exclusion list changes (new and different exclusions added on A_Database, or on B_Database, or on both

sides). Fig. 22 table is used in case of scenario 1. Fig. 23 table is used in case of scenario 2. Fig. 24 table is used in case of scenario 3 (Fig. 21 steps 854-856).

5 The analysis of records is now complete, and the records can be unloaded into their respective databases, including any additions, updates, or deletions. However, prior to doing so, the user is asked to confirm proceeding with unloading (Fig. 3, step 108-109). Up to this point, neither of the databases nor the History File have been
10 modified. The user may obtain through the Translation Engine's User Interface various information regarding what will transpire upon unloading.

15 If the user chooses to proceed with synchronization and to unload, the records are then unloaded in order into the B_Database, the A_Database and the History File. The Unloader modules 6,10 of the Translators 5,9 perform the unloading for the databases. The Synchronizer creates the History File and unloads the records into it. The Control Module 2 of the Translation Engine 1 first instructs the
20 B_Translator to unload the records from Workspace into the B_Database. Referring to ^{Figs. 25A and 25B} Fig. 25, for each CIG to be unloaded (determined in steps 902-907), based on the CIG_TYPE and which database it is unloading into (i.e., A or B), the unloader looks up in the table in ^{Figs. 26A-26D} Fig. 26 the
25 outcome that must be achieved by unloading - that is, whether to update, delete, add, or skip (Leave_Alone) (step 908). In steps 909-913, the unloader enforces date range restriction for a database subject to date range. The user may select, or a selection may be made by default, whether
30 to enforce the date range sternly or leniently. In case of stern enforcement, all records outside of the current date range would be deleted. This is useful for computers with

small storage capacity. In case of lenient enforcement, the records are left untouched.

Based on the result obtained from looking up the unloading outcome in the table, the unloader then either
5 adds a new record (steps 920-926), deletes an existing record (steps 914-919), or updates an existing record (steps 927-933). It should be noted that because we only update those fields which need to be updated (step 928), the fields which were sanitized but need not be updated are not
10 unloaded. Therefore, the values in those fields remain in unsanitized form in the database.

Referring to step 914, in some Applications when a Recurring Master must be added or updated, the record may have to be fanned out despite the ability of the Application
15 to support recurring records. For example, the Schedule+ Translator is generally able to put almost any Recurring Master Item into Schedule+ without fanning, but there are some exceptions. The Schedule+ Translator uses one Schedule section to handle all appointments and events. For
20 appointments, almost any recurrence pattern is allowed, but for events the only allowable true repeat type is YEARLY. DAILY recurring events can be dealt with by being translated into Schedule+ multi-day events which are not recurring but extend over several days by setting the EndDate some time
25 after the Start Date. But for the DAILY case there are restrictions. In particular exclusions in the midst of a multi-day Schedule+ event cannot be created. So the Translator decides that if section type is ToDos or the item is a non-Event Appointment, then the record need not be
30 fanned out. But if item is a YEARLY or DAILY with no exclusions then it can be stored as a Schedule+ yearly or daily event. Otherwise, it must be fanned.

37

Figs. 27A and 27B,

C Referring to ~~Fig. 27~~, steps 950-984 set out the preferred embodiment of fanning recurring records that must be updated. All cases fall within three scenarios, shown in Fig. 29.

5 In the first scenario a record which is a Recurring Master, and its counterpart in the other database is a Recurring Master, must be fanned now for its own database (steps 951-959). If the CIG_TYPE of the record is 132 (i.e. update both records), then it is changed to 13F which is a
10 special value specifically for this situation (step 951). For other CIG_Types, the CIG is broken into three singleton and given CIG_Types signifying their singleton status. In both of these cases, the function Fanning_For_Add (steps 986-996, described below) is called.

15 In the second scenario, the record was fanned previously and is going to be fanned now also. First, the dates of the instances are recorded in a temporary date array (steps 961-963). This array is compared to an array of the fanned instances of the recurrence pattern of the CIG
20 Recurring Master from the other database (steps 965-966). The dates which are not in the array of fanned instance are marked for deletion (step 967). The dates which are not in the temporary date array should be added to the unloading databases and therefore new FIG records are created for
25 those dates (steps 968-973). The dates which appear in both arrays are compared to the Synthetic Master and marked accordingly for UPDATE or Leave_Alone (steps 974-978).

In the third scenario, the record which was previously fanned should now be fanned also. The opposing
30 database's record in this scenario is also fanned instances. This is perhaps the most peculiar of the three cases. For example, a database may be able to handle multi-day (i.e. daily recurring) records but not any exclusion dates for

78b

database but were not used in synchronization are appended and unloaded as the Translator builds a new database for its Application.

5 The Control Module 3 next instructs the Synchronizer to create a new History File (step 112). Referring to Fig. 28, for every CIG in the Workspace, it is first determined which record should be unloaded to History File (steps 1001-1003). In the next step, Excl_Only flag is checked, which is set by the Merge_Exclusion_List logic (Fig. 21-24). If
10 that flag is set, a new record for unloading is created which has all fields taken from the History File record, except that the newly merged exclusion list is inserted into that record (step 1004). Before storing the record in the History File, all Flag Bits in the Extended Index are
15 cleared except the bit that indicating whether or not this is a recurring item (step 1005). The item is marked as a History File record to indicate its source. The CIG, FIG, and SKG are reset. All the HASH values and Start&EndDate&Time will be stored. All applicable unique ID
20 are also stored (Steps 1006-1009). The current record is then stored in the new History File (step 1010). If the current record is a Recurring Master for an ID-bearing FIG, we now store the whole FIG (i.e. all Fanned Instances) in the History File, with the FIG linkage words set in the
25 History File to hold the FIG records together (step 1011). Fanned instances which do not bear unique IDs are not stored in the History File since they can be re-generated by merely fanning out the Recurring Master.

30 Once all records are unloaded, various information necessary for identifying this History File and for the next synchronization are written into the History File (step 1013).

At this point Synchronization is complete.

Applications, such as scheduling Applications, often have more than one database. Each of these databases are known as sections. Each of these sections contain different data and must be synchronized with their corresponding sections in other Applications. However, there is not necessarily a one to one relationship between sections of various Applications. For example, Application A may comprise of the following sections: Appointments, Holidays, Business Addresses, Personal Addresses, and ToDo.

10 Application B however may comprise of the following sections: Appointments, Addresses, ToDo-Tasks, and ToDo-Calls. Although the general character of the sections are the same, there is not a one to one relation between the sections of these two Applications: Appointments and

15 Holidays in A contain the same type of data as Appointments in B; Business Addresses and Personal Addresses in A contain the same type of data as Addresses in B; and ToDo in A contains the same type of data as ToDo-Tasks and ToDo-Calls in B. Therefore, when synchronizing the sections of these

20 two Applications, it is necessary to synchronize at least two sections of one Application with one section of another Application.

The preferred embodiment performs this type of synchronization by providing for a number of section

25 categories: Appointment, ToDo, Note, Address, and General Database. All sections of a particular Application are studied and categorized according to this categorization. Therefore, in the above example of Application A, Appointments and Holidays are categorized Appointment type

30 sections (or database), Business Address and Personal Address as Address type sections, and ToDo as a ToDo type section.

For creating the map for mapping sections onto each other, an exact section match is always sought between sections of the two Applications. If not, one of the sections which were categorized as a section type is chosen to be the Main_Section among them. Other sections of the same type are referred to as subsections. All databases of the same type from the other Application will be mapped onto the Main_Section.

To properly synchronize from one time to the next, it is necessary to keep track of the source of records in the Main_Section. In the preferred embodiment, if a record in the Main_Section of the A_Application does not come from the Main_Section of the B_Application, one of fields in the record, preferably a text field, is tagged with a unique code identifying the subsection which is the source of the record. This is the record's Origin Tag. All records in the Workspace and the History File include a hidden internal field called _subType which contains the unique subsection code. Main_Section's field value in the preferred embodiment is zero so that it will not be tagged. When a record is loaded from a database into the Synchronization Workspace, the tag is stripped from the TagBearer field and put in the _subType field. If there is no tag, then the _subType is set to be the subType of the present section. If the TagBearer field is mapped then when reading records into the Workspace the tag, if any, is stripped from the TagBearer field value place it in _subtype.

Conversely when unloading records from the Workspace to a Database, the TagBearer field is tagged by a tag being added if the record is not from the Main_Section.

A Fast Synchronization database is a database which provides a method of keeping track of changes, deletions, and additions to its records from one synchronization to the

next. These databases speed up the synchronization process because only those records which have been modified need to be loaded from the database. Since the majority of records loaded by regular Translators are unchanged records, far
5 fewer records are loaded from the database into the Synchronizer.

Certain features are required for a database to be a Fast Synchronization database. The database records must have unique IDs and must have a mechanism for keeping track
10 of which records are added, changed, or deleted from synchronization to synchronization, including a list of deleted records. Unique IDs are required to accurately identify records over a period of time.

There are at least two ways to keep track of
15 additions, changes, and deletions in a database.

First, some databases maintain one Dirty bit per record which is a boolean flag that is set when a record is created or modified and is cleared when a function for clearing Dirty bits is called. Some databases offer a Clear
20 DirtyBit function that clears the bit of an individual record. Other databases offer a ClearDirtyBits function that clears the Dirty bits of all records in a database. The record-specific ClearDirtyBit function allows the preferred embodiment to use the database itself to keep
25 track of additions and changes.

The global ClearDirtyBits function forces the preferred embodiment to clear all Dirty bits at the conclusion of every Synchronization. Then as database edits are made by the user in between synchronizations, the
30 affected records are marked as Dirty. When Synchronization is performed again, only the Dirty records are loaded.

Second, some databases maintain a Date&Time stamp of when the record was added or last time the record was

modified. A Translator for such a database finds all records which were added or modified since the previous synchronization by searching for Date&Time stamps more recent than the Date&Time of the Last Synchronization.

5 A Fast Synchronization database must also keep track of deletions. This is done by maintaining a list of deleted records which can be read by a Translator.

A Translator sending Fast Synchronization database records to the Synchronizer provides only records which have
10 been changed, deleted, and added since the previous synchronization. Therefore, unlike a regular database Translator, a Fast Synchronization Translator does not provide the Synchronizer with unchanged records. Moreover, unlike a regular Translator it provides deleted records,
15 which the regular Translators does not.

In order for such databases to be synchronized without resorting to treating them as regular databases, the Synchronizer transforms Fast Synchronization records from the Translator into the equivalent regular database records.
20 These transformed records are then used by the Synchronizer in the synchronization. There are two transformations which are necessary. First, the Synchronizer needs to transform deleted records received from the Fast Synchronization Translator into a regular database deletions. Second,
25 synchronization needs to transform lack of output by the Fast Synchronization Translator into unchanged records.

The invention performs these transformations by using the History File. During the first synchronization, all records in the Fast Synchronization database are loaded
30 into the history file. As changes, additions, and deletions are made to the Fast Synchronization database, during each of the subsequent synchronizations the same change, additions, and deletions are made to the History File.

SECRET

44

Therefore, the History File at the end of each subsequent synchronization is an exact copy of the Fast Synchronization database.

When a Fast Synchronization Translator supplies no
5 input for a unique ID H_Record, the Synchronizer finds the corresponding H_Record in the Workspace and copies it into the Workspace as a record supplied as if it were loaded by the Fast Synchronization translator itself.

Referring to Fig. 30, steps 1050-1051, the
10 Synchronizer first verifies that there is an appropriate History File. Because the Fast Synchronizing process relies heavily on the History File, it is important to ensure that the same history file as the last Synchronization is used. Moreover, the History File is the background against which
15 the transformation of the Translator outputs into regular Translator outputs takes place. The History File keeps a date and time stamp of the last synchronization. Each of the Fast Synchronization database (if able to) and the Fast Synchronization Translator also stores the same date and
20 time stamp. The time and date stamp is used because it is unlikely that another History File will have exactly the same time and date entry, for the same two databases. It also identifies when last the Fast Synchronizer database and the History File contained the same records.

25 At the start of an incremental synchronization, the Synchronizer and the Fast Synchronization Translator compare date and time stamps. If time and date stamp synchronization parameters have changed since the previous synchronization, then the synchronization proceeds from
30 scratch (step 1052). In a synchronization from scratch all records in the Fast Synchronization database are loaded into the History File.

current and the previous date ranges. For a record marked as an addition, or during synchronizing from scratch, if the record falls outside the current date range, it is marked as Out_Of_Range (steps 1101 and 1153-1154). This record will
5 be written into the History File but not into the other database or take part in the synchronization. When the Fast Synchronization database records are loaded from the History File, if they fall outside of the previous date range, they are marked as Bystander (steps 1152-1157). If a Bystander
10 record forms a CIG with a Fast Synchronization record marked as a deletion or a change, the Bystander is marked with a Garbage flag because its field values serve no useful purpose any more: the record marked as DELETION should be deleted and the record marked as CHANGED should replace the
15 Bystander H Record (step 1162).

H_Records for which there are no inputs are transformed in the same manner as before (steps 1164-1165). If a Bystander record falls within the current date range, it is equivalent to a regular database record coming into
20 the current date range. Therefore, the H_Record is cloned and marked as a Fast Synchronizer record while the Bystander record is marked as Garbage (steps 1166-1171). Therefore, just like a new record of a regular database, it has no H Record counterpart.

25 If the user selects to abort a synchronization or
selects the option to ignore a conflict or conflicts in
general, some of the records loaded from the Fast
Synchronization database will not be accepted and recorded
in the History File. Therefore, the Translator should
30 provide that record again at the next synchronization.
However, because Fast Synchronization Translators supply
only records which have been changed, deleted, or added
since the previous synchronization, the records which were

